

# PRODUCT SPECIFICATIONS



## Main Unit

### Type

Color Laser Multifunctional

### Core Functions

Standard: Print, Copy, Scan, Send, Store  
 Optional: Fax

### Processor

Canon Dual Custom Processor (Shared)

### Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

### Memory

4.0 GB RAM

### Hard Disk Drive

Standard: 250 GB  
 Maximum: 1 TB

### Mirroring Hard Disk Drive

Optional: 250 GB, 1 TB  
 Method: Raid1

### Interface Connection

Network  
 Standard: 1000Base-T/100Base-TX/10Base-T,  
 Wireless LAN (IEEE 802.11 b/g/n)  
 Optional: NFC, Bluetooth Low Energy

### Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),  
 USB 2.0 x1 (Device)  
 Optional: Serial Interface, Copy Control Interface

### Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets  
 Maximum: 6,350 Sheets

### Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet  
 Stack Bypass  
 Optional: Dual 550-sheet Paper Cassettes  
 (CASSETTE FEEDING UNIT-AM1),  
 2,450-sheet High-Capacity Paper Cassette  
 (HIGH CAPACITY CASSETTE FEEDING  
 UNIT-A1), 2,700-sheet Paper Deck  
 (PAPER DECK UNIT-F1)

### Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets  
 Maximum: 3,450 Sheets  
 (with External Finisher and Copy Tray)

### Finishing Capabilities

Standard: Collate, Group  
 With Inner  
 Finisher: Collate, Group, Offset, Staple, Hole Punch,  
 Staple-Free Staple, Staple On Demand

### With External Finishers:

Collate, Group, Offset, Staple, Booklet, Hole  
 Punch, Staple-Free Staple, Staple On Demand

### Supported Media Types

Paper  
 Cassette 1: Thin, Plain, Recycled, Color, Heavy,  
 Pre-punched, Letterhead, Bond,  
 Transparency, Envelope

Paper  
 Cassette 2: Thin, Plain, Recycled, Color, Heavy,  
 Pre-punched, Letterhead, Bond,  
 Transparency, Tab, Envelope

Stack Bypass: Thin, Plain, Recycled, Color, Heavy,  
 Pre-punched, Labels, Letterhead,  
 Bond, Coated, Transparency, Tab,  
 Tracing,<sup>1</sup> Envelope

### Supported Media Sizes

Paper  
 Cassette 1: Letter, Executive, Statement-R, Envelope  
 [No.10 (COM10), DL, ISO-C5], Custom Size  
 (3-7/8" x 5-7/8" to 11-3/4" x 8-1/2")

Paper  
 Cassette 2: 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
 Executive, Statement-R, Envelope [No.10  
 (COM10), Monarch, DL, ISO-C5], Custom Size  
 (3-7/8" x 7-1/8" to 12" x 18")

Stack Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18"), Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18"), Free Size (3-7/8" x 5-1/2" to 12-5/8" x 18")

**Supported Media Weights**

Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)  
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)

**Warm-up Time**

From Power On: Approx. 10 Seconds<sup>2</sup>  
From Sleep Mode: Approx. 10 Seconds<sup>3</sup>  
Quick Startup Mode: Approx. 4 Seconds<sup>4</sup>

**Dimensions (W x D x H)**

24-3/8" x 29-1/4" x 37-3/8"(620 mm x 742 mm x 950 mm)<sup>5</sup>

**Installation Space (W x D)**

Basic: Stack Bypass + Cassette Drawers open: 37-1/8" x 46-3/8" (943 mm x 1,176 mm)

**Weight**

310.9 lb. (141 kg)<sup>6</sup>

**Print Specifications**

**Print Speed (BW and Color)**

C5560i III: Up to 60 ppm (Letter); Up to 36 ppm (Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")  
C5550i III: Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (11" x 17")  
C5540i III: Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")  
C5535i III: Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17")

**Print Resolution (dpi)**

1200 x 1200, 600 x 600

**Standard Page Description Languages**

UFR II, PCL®6, Adobe® PS® 3

**Direct Print**

Available from USB, Advanced Box, Remote UI, and Web Access<sup>7</sup>

**Supported File Types**

PDF, TIFF, JPEG, EPS,<sup>8</sup> XPS

**Printing from Mobile Devices and Cloud-based Services**

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

**Fonts**

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),<sup>9</sup> Barcode Fonts<sup>10</sup>  
PS fonts: 136 Roman

**Operating System<sup>11</sup>**

UFR II: Windows® Server 2008/Windows® 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.9 or later)  
PCL: Windows Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016  
PS: Windows Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.9 or later)  
PPD: MAC OS X (10.3.9 or later), Windows 7/8.1/10

**Print Features**

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Forced Hold Printing, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing

**Copy Specifications**

**Copy Speed (BW and Color)**

C5560i III: Up to 60 ppm (Letter); Up to 36 ppm (Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")  
C5550i III: Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (11" x 17")  
C5540i III: Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")  
C5535i III: Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17")

**First-Copy-Out Time (Letter)**

C5560i III: As fast as 2.9 seconds (BW)/4.5 seconds (Color)  
C5550i III: As fast as 3.5 seconds (BW)/5.2 seconds (Color)  
C5540i III: As fast as 4.1 seconds (BW)/6.1 seconds (Color)  
C5535i III: As fast as 4.9 seconds (BW)/7.4 seconds (Color)

**Copy Resolution (dpi)**

Reading: 600 x 600  
Printing: 1200 x 1200

**Multiple Copies**

Up to 999 Copies

**Copy Exposure**

Automatic or Manual (9 Levels)

**Magnification**

25%-400% (1% Increments)

**Preset Reductions**

25%, 50%, 64%, 73%, 78%

**Preset Enlargements**

121%, 129%, 200%, 400%

**Basic Copy Features**

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

**Special Copy Features**

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed, Free Size Original, Color Balance, Adjust One-Touch Color, Area Designation

**Scan Specifications**

**Type**

Color Platen and Single-pass Duplexing Automatic Document Feeder

**Document Feeder Paper Capacity**

150 Sheets (20 lb. Bond)

**Document Feeder Supported Media Sizes**

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 5" x 5-1/2" to 12" x 17"

**Document Feeder Supported Media Weights**

BW Original: 13 lb. Bond to 58 lb. Cover (50 to 157 g/m<sup>2</sup>)  
CL Original: 17 lb. Bond to 58 lb. Cover (64 to 157 g/m<sup>2</sup>)

**Platen Acceptable Originals**

Sheet, Book, 3-Dimensional Objects [Height: up to 2" (50 mm), Weight: Up to 4.4 lb. (2kg)]

**Pull Scan**

Color Network ScanGear2 for both Twain and WIA  
Supported OS: Windows 7/8.1/10  
Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

**Scan Resolution (dpi)**

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

**Scan to Mobile Devices and Cloud-based Services**

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

**Scan Speed (Letter)**

Single-sided Scanning (BW): 80 ipm (300 dpi)/80 ipm (600 dpi)  
Single-sided Scanning (Color): 80 ipm (300 dpi)/60 ipm (600 dpi)  
Double-sided Scanning (BW): 160 ipm (300 dpi)/150 ipm (600 dpi)  
Double-sided Scanning (Color): 160 ipm (300 dpi)/80 ipm (600 dpi)

**Send Specifications**

**Destination**

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

**Color Mode**

Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and-White), Full color, Grayscale, and Black-and-White

**Address Book**

LDAP (2,000)/Local (1,600)/Speed dial (200)

**Send Resolution (dpi)**

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

**Communication Protocol**

File: FTP (TCP/IP), SMB v3.0, WebDAV  
Email: SMTP, POP3

**File Format**

Standard: TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b), Limited Color, Device Signature, XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint®, Word)  
Optional: PDF (Trace & Smooth, User Signature), XPS (User Signature)

**Universal Send Features**

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

**Fax Specifications**

**Maximum Number of Connection Lines**

4

**Modem Speed**

Super G3: 33.6 kbps  
G3: 14.4 kbps

**Compression Method**

MH, MR, MMR, JBIG

**Resolution (dpi)**

400 x 400, 200 x 400, 200 x 200, 200 x 100

**Sending/Recording Size**

Statement-R to 11" x 17"

**Fax Memory**

Up to 30,000 Pages

**Speed Dials**

Max. 200

**Group Dials/Destinations**

Max. 199 Dials

**Sequential Broadcast**

Max. 256 Addresses

**Memory Backup**

Yes

**Fax Features**

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

## Store Specifications

### Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

### Advanced Box

Communication Protocol: SMB or WebDAV  
Supported  
Client PC: Windows (Windows 7/8.1/10)  
Concurrent Connections (Max.)  
SMB: 64  
WebDAV: 3 (Active Sessions)

### Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)  
Approx. 480 GB (With Optional 1 TB HDD)

### Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

### Memory Media

Standard: USB

## Security Specifications

### Authentication

Standard: Universal Login Manager, uniFLOW Online Express,<sup>12</sup> User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in  
Optional: uniFLOW

### Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup  
Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

### Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

### Document

Standard: Secure Watermark, Encrypted PDF, Encrypted Secure Print, Digital Signatures, Adobe LiveCycle® Rights Management ES2.5 Integration  
Optional: User Signatures, Document Scan Lock

## Environmental Specifications

### Operating Environment

Temperature: 50 to 86 °F  
Humidity: 20 to 80 % RH (Relative Humidity)

### Power Requirements

C5560i III/  
C5550i III: 120-127V AC 60 Hz, 11.5 A  
C5540i III/  
C5535i III: 120-127V AC, 60 Hz, 10 A

### Plug (Main Unit)

C5560i III/  
C5550i III: NEMA 5-20P  
C5540i III/  
C5535i III: NEMA 5-15P

### Power Consumption

Maximum: Approx. 1,800 W  
Standby: Approx. 65.2 W<sup>13</sup>  
Sleep Mode: Approx. 0.8 W<sup>14</sup>  
Typical Electricity Consumption (TEC) Rating:  
C5560i III: 3.2 kWh  
C5550i III: 2.5 kWh  
C5540i III: 2.0 kWh  
C5535i III: 1.6 kWh

### Standards

ENERGY STAR® Certified  
Rated EPEAT® Gold<sup>15</sup>

## Consumables

### Toner

GPR-55 Toner<sup>16</sup>

### Toner Yield (Estimated @ 6% Coverage)

Black: 69,000 Images  
Color (C,M,Y):<sup>16</sup> 60,000 Images

## Fiery Print Controller Specifications (Optional)

### imagePASS-P2 (Embedded)

#### System

Fiery FS350

#### Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

#### Standard Page Description Languages

PCL6, Adobe PS 3

#### Memory

4 GB

#### Hard Disk Drive

500 GB

#### Processor

Pentium G4400 (3.3 GHz)

#### Fonts

PS: 138 Adobe PS Fonts  
PCL: 113 PCL Fonts

#### Supported Operating Systems

Windows 7 (32 and 64 bit)/Windows 8.1 (32 and 64 bit)/Windows 10 (32 and 64 bit)/Windows Server 2012 (64 bit only)/Windows Server 2012 R2 (64 bit only)/Windows Server 2016 R2 (64 bit only)/MAC OS (10.11 or Higher)

#### Interface

2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB x 3.0 x 2 (Rear x 2), USB x 2.0 x 4 (Rear x 4)

#### Network Protocols

TCP/IP FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNMP, 802.1X, DHCP, DNS, NTP

#### Fiery Print Controller Features

Fiery Command Workstation 6, Paper Catalog, Fiery Spot On, Fiery Remote Scan

#### Fiery Print Controller Options

Fiery Impose, Fiery Compose, Fiery Impose and Compose, Productivity package Web activate (includes Fierd JDF), Fiery Hot Folders, and Virtual Printers

#### Direct Print

PDF 1.7, EPS, TIFF 6, JDF 1.4/JMF (OP)

#### VDP

FreeForm v1, 2.1

#### Dimensions (W x D x H)

11-1/4" x 3-5/8" x 11-5/8" (285 mm x 93 mm x 295 mm)

## Paper Supply Options

### CASSETTE FEEDING UNIT-AM1

Paper Capacity: 550 Sheets x 2 Cassettes [20 lb. Bond (80 g/m<sup>2</sup>)]  
Paper Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, and Custom Size [3-7/8" x 7-1/8" to 12" x 18" (98.0 x 182.0 to 304.8 x 457.2 mm)]  
Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Power Source: From the Main Unit  
Dimensions (W x D x H): 24-3/8" x 27-5/8" x 9-7/8" (620 mm x 700 mm x 251 mm)  
Weight: Approx. 49.6 lb. (22.5 kg)

### HIGH-CAPACITY CASSETTE FEEDING UNIT-A1

Paper Capacity: 2,450 sheets [20 lb. Bond (80 g/m<sup>2</sup>)]  
Paper Size: Letter  
Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Power Source: From the Main Unit  
Dimensions (W x D x H): 24-3/8" x 27-5/8" x 9-7/8" (620 mm x 700 mm x 251 mm)  
Weight: 66.1 lb. (30 kg)

### PAPER DECK UNIT-F1

Paper Capacity: 2,700 Sheets [20 lb. Bond (80 g/m<sup>2</sup>)]

Paper Size: Letter  
Paper Weight: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Power Source: From the Main Unit  
Dimensions (W x D x H): 13-1/2" x 24-7/8" x 17-3/8" (344 mm x 630 mm x 440 mm)  
Weight: 68.3 lb. (31 kg)

## Output Options

### INNER 2-WAY TRAY-J1

Number of Trays: 2  
Total Output Capacity: Upper Tray: 100 Sheets  
Lower Tray: 250 Sheets  
Paper Weight: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)  
Paper Size: Standard size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18")  
Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18")  
Weight: Approx. 1.3 lb (0.6 kg)

### INNER FINISHER-H1

Number of Trays: 2  
Top Tray Capacity:<sup>17</sup> Letter/Statement/Statement-R/Executive (45 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (45 Sheets)  
Lower Tray Capacity:<sup>17</sup> Letter/Statement/Statement-R/Executive (500 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (250 Sheets)  
Paper Weight: 14 lb. Bond to 110 lb. Index (52 to 300 g/m<sup>2</sup>)  
Acceptable Paper Weight: 14 lb. Bond to 140 lb. Cover (52 to 256 g/m<sup>2</sup>)  
Staple Position: Corner, Double  
Staple Capacity: Corner Staple and Double Staple  
Letter/Executive: 50 Sheets (14 to 24 lb. Bond) 11" x 17"/Legal/Letter-R: 30 Sheets (14 to 24 lb. Bond)  
Staple-Free Staple 11"x17"/Letter: 5 Sheets (14 to 17 lb. Bond) 4 Sheets (17.3 to 21.7 lb. Bond) 3 Sheets (21.7 to 28 lb. Bond)

Staple On Demand: 40 Sheets [20 lb. Bond (80 g/m<sup>2</sup>)]  
Power Source: From the Main Unit  
Weight: Approx. 19 lb (8.6 kg)

### STAPLE FINISHER-Y1 (External)

Number of Trays: 2  
Top Tray Capacity:<sup>17</sup> Letter/Executive/Statement/Statement-R (3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)  
Lower Tray Capacity:<sup>17</sup> Letter/Executive/Statement/Statement-R (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)

Paper Weight: Top Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Lower Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)

Staple Position: Corner, Double

Staple Capacity: Corner Staple and Double Staple  
Letter/Executive: 50 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
11" x 17"/Legal/ Letter-R: 30 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
Staple-Free Staple: 11"x17"/Letter: 5 Sheets [14 to 17 lb. Bond (52 to 64 g/m<sup>2</sup>)] 4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m<sup>2</sup>)] 3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m<sup>2</sup>)]

Staple On Demand: 50 Sheets [24 lb. Bond (90 g/m<sup>2</sup>)]  
Power Source: From the Main Unit  
Dimensions (W x D x H): 25-1/8" x 24-1/2" x 45" (637 mm x 623 mm x 1142 mm)  
Weight: Approx. 68.3 lb (31 kg)

## BOOKLET FINISHER-Y1 (External)

Number of	3
Trays:	
Top Tray	Letter/Executive/Statement/Statement-R
Capacity: <sup>17</sup>	(3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)
Lower Tray	Letter/Executive/Statement/Statement-R
Capacity: <sup>17</sup>	(250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)
Paper Weight	
Top Tray:	14 lb. Bond to 140 lb. Index (52 to 256 g/m <sup>2</sup> )
Lower Tray:	14 lb. Bond to 110 lb. Cover (52 to 300 g/m <sup>2</sup> )
Staple Position:	Corner, Double
Staple Capacity	
Corner Staple and Double Staple	
Letter/	50 Sheets [24 lb. Bond (90 g/m <sup>2</sup> )]
Executive:	
11" x 17"/Legal/	30 Sheets [24 lb. Bond (90 g/m <sup>2</sup> )]
Letter-R:	
Staple-Free Staple	
11"x17"/Letter:	5 Sheets [14 to 17 lb. Bond (52 to 64 g/m <sup>2</sup> )] 4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m <sup>2</sup> )] 3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m <sup>2</sup> )] 50 Sheets [24 lb. Bond (90 g/m <sup>2</sup> )]
Staple On	
Demand:	
Booklet-Stitch	12" x 18", 11" x 17", Legal, Letter-R,
Paper Size:	Custom Size [7-3/4" x 10-5/8" to 12" x 18" (195 mm x 270 mm to 304.8 mm x 457.2 mm)]
Booklet-	20 Sheets x 10 Sets [22 lb. Bond (81 g/m <sup>2</sup> )]
Stitch Staple	(including one cover sheet up to 140 lb.) Index
Capacity:	(256 g/m <sup>2</sup> )
Power Source:	From the Main Unit/85.6 W
Dimensions	25-1/8" x 24-1/2" x 45"
(W x D x H):	(637 mm x 623 mm x 1142 mm)
Weight:	Approx. 125.7 lb (57 kg)

## INNER 2/3-HOLE PUNCHER-B1

(Requires the INNER FINISHER-H1)

Acceptable	
Punch Paper	14 lb. Bond to 110 lb. Cover
Weight:	(52 to 300 g/m <sup>2</sup> )
Acceptable Punch Paper Size	
Two Holes:	11" x 17", Legal, Letter, Letter-R, Executive
Three Holes:	11" x 17", Letter, Executive
Power Source:	From the Main Unit

## 2/3-HOLE PUNCHER-A1

(Requires either the STAPLE FINISHER-Y1 or BOOKLET FINISHER-Y1)

Acceptable	
Punch Paper	14 lb. Bond to 110 lb. Cover
Weight:	(52 to 300 g/m <sup>2</sup> )

Acceptable Punch Paper Size

Two holes:	11" x 17", Legal, Letter, Letter-R, Executive
Three holes:	11" x 17", Letter, Executive
Power Source:	From the Main Unit

## Hardware Options

### Card Readers

MICARD PLUS PROXIMITY CARD READER  
COPY CARD READER-F1  
COPY CARD READER ATTACHMENT-B5

### Others

CABINET TYPE-N  
BUFFER PASS UNIT-L1  
COPY TRAY-J2  
UTILITY TRAY-B1  
PLATEN COVER TYPE W  
PRINTER COVER-J1  
TAB FEEDING ATTACHMENT-F1  
USB KEYBOARD

## Security Options

### Document Security

DOCUMENT SCAN LOCK KIT-B2  
iR-ADV SECURITY KIT-P1 FOR IEEE 2600.1 COMMON  
CRITERIA CERTIFICATION<sup>18</sup>

### Data Security

HDD MIRRORING KIT-J1  
2.5"/250 GB HDD-N1  
2.5"/1 TB HDD-P1  
REMOVABLE HDD KIT-AL1

## System and Controller Options

### Print Accessories

PCL INTERNATIONAL FONT SET-A1

### Barcode Printing

BARCODE PRINTING KIT-D1

### EFI-Fiery Based Controller

imagePASS-P2  
REMOVABLE HARD DISK DRIVE KIT-B1  
FIERY IMPOSE  
FIERY COMPOSE  
FIERY IMPOSE AND COMPOSE

### System Accessories

COPY CONTROL INTERFACE KIT-A1  
CONNECTION KIT-A1 FOR BLUETOOTH LE  
NFC KIT-C1  
MEAP WEB CONNECTION KIT-V5.3<sup>19</sup>

### Fax Accessories

SUPER G3 FAX BOARD-AS2

SUPER G3 2ND LINE FAX BOARD-AS2

SUPER G3 3RD/4TH LINE FAX BOARD-AS2

REMOTE FAX KIT-A1

IP FAX EXPANSION KIT-B1

## Other Options

### Accessibility Accessories

ADF ACCESS HANDLE-A1  
VOICE GUIDANCE KIT-G1  
VOICE OPERATION KIT-D1  
BRAILLE LABEL KIT-F1

### Staples

STAPLE-P1<sup>20</sup>

STAPLE CARTRIDGE-Y1<sup>21</sup>

<sup>1</sup> Some types of tracing paper cannot be used.

<sup>2</sup> Time from device power-on to when copy jobs can be programmed with Quick Start Up mode.

<sup>3</sup> Time from exiting Sleep mode to when printing is operational.

<sup>4</sup> Time from device power-on to when key operation can be performed on the touch screen.

<sup>5</sup> Includes main unit and either Cassette Feeding Unit-AM1, High Capacity Cassette Feeding Unit-A1, or Cabinet Type-N.

<sup>6</sup> Includes main unit, consumables, and Cassette Feeding Unit-AM1.

<sup>7</sup> PDF print from Web sites is supported.

<sup>8</sup> EPS can be printed directly only from the Remote User Interface.

<sup>9</sup> Requires the optional PCL International Font Set-A1.

<sup>10</sup> Requires the optional Barcode Printer Kit-D1.

<sup>11</sup> Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

<sup>12</sup> No charge for this solution; however activation is required.

<sup>13</sup> Reference value (measured one unit).

<sup>14</sup> 0.8 W sleep mode not available in all circumstances due to certain settings.

<sup>15</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit [www.epeat.net](http://www.epeat.net).

<sup>16</sup> GPR-55L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 26,000 images.

<sup>17</sup> With 20 lb. Bond (80 gsm) paper.

<sup>18</sup> Will launch at a later date.

<sup>19</sup> No charge for this option; however it does need to be ordered.

<sup>20</sup> Used for corner/double stapling only. 2 cartridges per case. 5,000 staples per cartridge.

<sup>21</sup> Used for booklet finishing only. 3 cartridges per case. 2,000 staples per cartridge.

USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.  
©2019 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

0119-IRA5511xxSS-PDF-IH



To learn about Canon's many awards, visit [usa.canon.com/awards](http://usa.canon.com/awards).

