













Environmental Profile Sheet

The imageRUNNER ADVANCE C5560i III/C5550i III/C5540i III/C5535i III models incorporate Canon technologies. Canon has a strong environmental focus at every stage of the product life cycle—Produce, Use, and Recycle. The technologies below focus on Energy Conservation, Resource Conservation, and Pollution Prevention, form the foundation of Canon's Environmental Management System.

	Energy Conservation	Resource Conservation	Pollution Prevention
In order to help reduce dependence on petroleum-based materials, Canon uses 100% recycled plastics* and bio-based plastics on certain exterior parts.			
A variety of sleep recovery triggers, including motion sensing, help encourage the use of Sleep Mode , help minimize power consumption.			
Power consumption in Sleep Mode is as low as 0.80 W!			
Low Typical Electricity Consumption (TEC) values , which measure power consumption during a one-week period.			
Power consumption is reduced by utilizing White LED array technology in its Color Image Reader versus using a traditional Xenon tube!			
Power consumption is reduced by utilizing Canon Image Sensor technology versus using traditional CCD sensors! Advanced Color RAPID Fusing technologies help reduce power consumption and limit the warm-up period .			
CS Toner, with its low melting point, helps reduce fusing temperature requirements .			
All suppliers are required to meet Canon's stringent Green Procurement policy and environmental terms. This helps Canon exceed the tough European Union's RoHS Directive, which controls/restricts the use of certain hazardous substances .			
Each system is equipped with paper-, toner-, and energy-saving features that help to cut costs and conserve resources .			
Long-life parts and high-yield supplies help maximize uptime and help reduce the amount of materials consumed during the product life cycle.			

Canon. The Natural Partner for Business.



* Excluding a small amount of additives to improve physical properties.

Environment-Related Specifications

System Type

Color Laser Multifunctional

Functions

Standard:	Print (UFR III, PCL® 6, Adobe® PostScript® 3™), Copy, Scan, Send, Store
Optional:	Fax (Up to 4 lines)

Operation Panel

10.1" TFT LCD WSVGA Color Flat-panel

Warm-up Time

From Power On:	Approx. 10 Seconds
From Sleep Mode:	Approx. 10 Seconds
Quick Startup Mode:	Approx. 4 Seconds

Power Requirements

C5560i III/C5550i III:	120-127 V AC, 60 Hz, 11.5 A
C5540i III/C5535i III:	120-127 V AC, 60 Hz, 10 A

Power Consumption

Maximum:	1,800 W
Sleep Mode:	0.80 W
Copying/Printing:	959 W
Copy Ready (Standby):	65 W
Plug-in:	0.450 W

One Week TEC

C5560i III: 3.2 kWh	C5540i III: 2.0 kWh
C5550i III: 2.5 kWh	C5535i III: 1.6 kWh

One Year TEC

C5560i III: 166.4 kWh	C5540i III: 104.0 kWh
C5550i III: 130.0 kWh	C5535i III: 83.2 kWh

British Thermal Units (BTU)

Maximum (BTU/Hr.):	6,142
Copying/Printing (BTU/Hr.):	3,273
Copy-Ready (Standby) (BTU/Hr.):	222

Plug

C5560i III/C5550i III:	NEMA 5-20P
C5540i III/C5535i III:	NEMA 5-15P

Dimensions (W x D x H)

24-3/8" x 29-1/4" x 37-3/8" (620 mm x 742 mm x 950 mm)

Installation Space (W x D)

Basic (Stack Bypass + Cassette Drawers open):
37-1/8" x 46-3/8" (943 mm x 1176 mm)*

Weight

Approx. 310.9 lb. (141 kg)**

Noise Levels

Standby

C5560i III: 37.1 dB or Less	C5540i III: 37.3 dB or Less
C5550i III: 36.9 dB or Less	C5535i III: 36.9 dB or Less

Copying/Printing

C5560i III/C5550i III:	75 dB or Less
C5540i III:	73 dB or Less
C5535i III:	71.5 dB or Less

Recycled Content

Recycled Primary Package (%)***	Approx. 22%
Post-consumer Waste:†	0.1%
Secondary Waste Materials:††	0.0%
Recycled PETE Product:†††	0.0%

Recycled Paper Support

100% Post-consumer Content:	Yes
-----------------------------	-----

Environmental Standards Compliance

ENERGY STAR® Certified
EPEAT® Gold
EU RoHS Compliant
Ecomark▲
Blue Angel▲▲

Environment-conscious Features

Two-sided, Copy Sample, Confirmation/Cancel, Image Combination, ID Card Copy, Secured Print, Job Forwarding, Department ID Management, Access Management System, Authentication (Universal Login Manager), Standard Duplex Driver, Auto/Weekly Sleep Timer, Auto/Weekly Shutdown Timer, Staple-Free Stapling (Optional)

* Includes Main Unit and either Cassette Feeding Unit-AM1, High-Capacity Cassette Feeding Unit-A1, or Cabinet Type-N.

** Including consumables.

*** Percentage based on weight of recycled content.

† The percentage of plastics the device contains that's derived from recycled plastic materials (by weight).

†† The percentage of reused waste material.

††† The percentage of recycled PETE material.

▲ This regulation is for the EU model product.

▲▲ This regulation is for the Japanese model.

USA.CANON.COM/ENERGYSTAR

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these model as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. PostScript® 3™ is either a registered trademark or trademark of Adobe Systems Incorporated in the United States and/or other countries. PCL 6 is a trademark of Hewlett Packard Company. Canon, imageRUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2019 Canon U.S.A., Inc. All rights reserved.

0119-C5500IIISRSEPS-PDF-IH

