













Environmental Profile Sheet

Canon's imageRUNNER ADVANCE C3530i III/C3525i III models incorporate those technologies with a strong environmental focus at every stage of the product life cycle—Produce, Use, and Recycle. The technologies listed below focus on Energy Conservation, Resource Conservation, and Pollution Prevention and form the foundation of Canon's Environmental Management System.

	Energy Conservation	Resource Conservation	Pollution Prevention
In order to help reduce dependence on petroleum-based materials, Canon uses 100% recycled plastics* and bio-based plastics on certain exterior parts.			
A variety of sleep recovery triggers, including motion sensing, help encourage the use of Sleep Mode , helping to minimize power consumption.			
Power consumption in Sleep Mode is as low as 0.80 W!			
Low Typical Electricity Consumption (TEC) values , which measure power consumption during a one-week period.			
Power consumption is reduced by utilizing White LED array technology in its Color Image Reader versus using a traditional Xenon tube!			
RAPID Fusing technologies help reduce power consumption and limit the warm-up period .			
pQ Toner, with its low melting point, helps reduce fusing temperature requirements .			
All suppliers are required to meet Canon's stringent Green Procurement policy and environmental terms. This helps Canon exceed the tough European Union's RoHS Directive, which controls/restricts the use of certain hazardous substances .			
Each system is equipped with paper-, toner-, and energy-saving features that help to cut costs and conserve resources .			
Long-life parts and high-yield supplies help maximize uptime and help reduce the amount of materials consumed during the product life cycle.			

Canon. The Natural Partner for Business.



* Excluding a small amount of additives to improve physical properties.

Environment-Related Specifications

System Type

Color Laser Multifunctional

Functions

Standard:	Print (UFR III, PCL® 6, Adobe® PostScript® 3™), Copy, Scan, Send, Store
Optional:	Fax (Up to two lines)

Operation Panel

10.1" TFT LCD WSVGA Color Flat-panel

Warm-up Time

From Power On:	Approx. 10 Seconds
From Sleep Mode:	Approx. 10 Seconds
Quick Startup Mode	Approx. 4 seconds

Power Requirements

120-127 V AC, 60 Hz, 7.5 A

Power Consumption

Maximum:	1,500 W
Sleep Mode:	0.80 W
Copying/Printing:	C3530i III: 550 W C3525i III: 548.3 W
Copy Ready (Standby):	43 W
Plug-in:	0.40 W
One Week TEC:	C3530i III: 1.2 kWh C3525i III: 1.0 kWh
One Year TEC:	C3530i III: 62.4 kWh C3525i III: 52.0 kWh

British Thermal Units (BTU)

Maximum (BTU/Hr.):	5,119
Copying/Printing (BTU/Hr.):	C3530i III: 1,911 C3525i III: 1,835

Copy-Ready (Standby) (BTU/Hr.): 147

Plug: NEMA 5-15P

Dimensions (W x D x H)

22-1/4" x 29-1/4" x 45-1/5" (565 mm x 742 mm x 1148 mm)*

Installation Space (W x D)

Basic [With ADF (Stack Bypass and Cassette Drawers Open)]:
38-1/2" x 44-1/4" (978 mm x 1123 mm)
Fully Configured: 63-3/4" x 44-1/4" (1620 mm x 1123 mm)**

Weight

Approx. 213.8 lb. (97 kg)***

Noise Levels

Standby:	C3530i III: 24.7 dB or Less C3525i III: 23.9 dB or Less
Copying/Printing:	C3530i III: 70.0 dB or Less C3525i III: 68.5 dB or Less

Recycled Content

Recycled Primary Package (%): [▲]	Approx. 37%
Post-consumer Waste: [†]	0.01%
Secondary Waste Materials: ^{††}	0.0%
Recycled PETE Product: ^{†††}	0.0%

Recycled Paper Support

100% Post-consumer Content: Yes

Environmental Standards Compliance

ENERGY STAR® Certified

EPEAT® Gold

EU RoHS Compliant[◆]Ecomark^{◆◆}Blue Angel[◆]

Environment-conscious Features

Two-sided, Copy Sample, Confirmation/Cancel, Image Combination, ID Card Copy, Secured Print, Job Forwarding, Department ID Management, Access Management System, Authentication (Universal Login Manager), Standard Duplex Driver, Auto/Weekly Sleep Timer, Auto/Weekly Shutdown Timer, Staple-Free Stapling (Optional)

* Includes Main Unit and either Cassette Feeding Unit-AP1 or Cabinet Type-R.

** Includes Main Unit and either Cassette Feeding Unit-AP1 or Cabinet Type-R and Staple/Booklet Finisher-AA1.

*** Includes Main Unit, Consumables, and Cassette Feeding Unit-AP1.

▲ Percentage based on weight of recycled content.

† The percentage of plastics the device contains that's derived from recycled plastic materials (by weight).

†† The percentage of reused waste material.

††† The percentage of recycled PETE material.

◆ The percentage of reused waste material.

◆◆ The percentage of recycled PETE material.

USA.CANON.COM/ENERGYSTAR

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks of the EPA. PostScript® 3™ is either a registered trademark or trademark of Adobe Systems Incorporated in the United States and/or other countries. PCL 6 is a trademark of Hewlett Packard Company. Canon, imageRUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2019 Canon U.S.A., Inc. All rights reserved.

0119-35001111SRSEPS-PDF-IH

